

SECTION 1: Identification

1.1. Identification

Product form	: Substance
Substance name	: Aromatic 100
CAS-No.	: 64742-95-6
Product code	: Complex Substance
Synonyms	: Naphtha, C8 bis C10 / solvent naphtha (petroleum), light aromatic / aromatic hydrocarbon

1.2. Recommended use and restrictions on use

Recommended use	: Industrial use Solvent
Restrictions on use	: None known

1.3. Supplier

<u>Atlanta Branch Office</u>	<u>Ocoee Branch Office</u>	<u>Spartanburg Branch Office</u>
Whitaker Oil Company	Whitaker Oil Company	Whitaker Chemicals LLC
1557 Marietta Road NW	280 Enterprise Street	405 John Dodd Road
Atlanta, GA 30318	Ocoee, FL 34761	Spartanburg, SC 29303
404-355-8220 (t)	407-656.0088 (t)	864-578-6968 (t)
404-355-2436 (f)	407-877-8335 (f)	864-578-6864 (f)

WEBSITE: www.whitakeroil.comEMAIL: SDS@whitakeroil.com

1.4. Emergency telephone number

Emergency number : **CHEMTREC** 800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Germ cell mutagenicity Category 1B	H340	May cause genetic defects
Carcinogenicity Category 2	H351	Suspected of causing cancer (Inhalation)
Specific target organ toxicity (single exposure) Category 3	H335	May cause respiratory irritation
Specific target organ toxicity (single exposure) Category 3	H336	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 1	H372	Causes damage to organs through prolonged or repeated exposure
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Aromatic 100

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: H226 - Flammable liquid and vapor H304 - May be fatal if swallowed and enters airways H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H351 - Suspected of causing cancer (Inhalation)
Precautionary statements (GHS-US)	: P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking P233 - Keep container tightly closed P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical, lighting, ventilating equipment P242 - Use only non-sparking tools P243 - Take precautionary measures against static discharge P260 - Do not breathe mist, vapors P261 - Avoid breathing mist, vapors P264 - Wash Skin thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective clothing, protective gloves, eye protection, face protection P301+P310 - If swallowed: Immediately call a POISON CENTER or doctor/physician P302+P352 - IF ON SKIN: Wash with plenty of soap and water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P308+P313 - If exposed or concerned: Get medical advice/attention P312 - Call a POISON CENTER or doctor/physician if you feel unwell P314 - Get medical advice/attention if you feel unwell P331 - Do NOT induce vomiting P332+P313 - If skin irritation occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P370+P378 - In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish P403+P233 - Store in a well-ventilated place. Keep container tightly closed P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of contents/container in accordance with local, regional, national, and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

This material is defined as a complex substance

Name	: Aromatic 100
CAS-No.	: 64742-95-6
	Solvent Naphtha (Petroleum), Light Aromatic
	Concentration: 100%

Hazardous Constituent(s) Contained in Complex Substance(s) required for disclosure	Product identifier	%	GHS-US classification
Pseudocumene (1,2,4-Trimethylbenzene)	(CAS-No.) 95-63-6	< 32	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 STOT SE 3, H335 Aquatic Chronic 2, H411

Aromatic 100

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazardous Constituent(s) Contained in Complex Substance(s) required for disclosure	Product identifier	%	GHS-US classification
Xylene	(CAS-No.) 1330-20-7	< 2.2	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Carc. 2, H351 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Cumene	(CAS-No.) 98-82-8	< 1.1	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after ingestion : Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Fire hazard : Flammable liquid and vapor.
- Reactivity : Flammable liquid and vapor.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

Aromatic 100

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Aromatic 100 (64742-95-6)		
ACGIH	Local name	Cumene
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & URT irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Cumene (98-82-8)		
ACGIH	Local name	Cumene
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & URT irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Pseudocumene (95-63-6)		
ACGIH	ACGIH TWA (ppm)	25 ppm
Xylene (1330-20-7)		
ACGIH	Local name	Xylene
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Aromatic 100

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the supplier for additional information.

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following color(s): Colorless
Odor	: Aromatic odor
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: <= 322 °F
Flash point	: <= 115 °F
Relative evaporation rate (butyl acetate=1)	: 0.27
Flammability Limits	: LEL: 0.9 UEL: 6.2
Vapor density (Air =1)	: 4.2 at 101 kPa
Vapor pressure at 20 °C	: 0.269 kPa (2.02 mmHg) 0.815 kPa (6.13 mmHg) at 38 °C
Relative vapor density at 20 °C	: No data available
Relative density	: 0.874 (at 15.6 °C) (7.29 lbs/
Specific gravity / density	: 0.87 - 0.89
Solubility	: Water: < 0.01 g/100ml
Log Pow	: 2.1 - 6
Auto-ignition temperature	: 905 °F
Decomposition temperature	: No data available
Viscosity, kinematic	: 0.75 cSt @ 40°C
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

Aromatic 100

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Harmful if inhaled.

Aromatic 100 (64742-95-6)	
LD50 oral rat	3492 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
ATE US (oral)	3492 mg/kg body weight
ATE US (dust, mist)	4.386 mg/l/4h

Cumene (98-82-8)	
LD50 oral rat	> 2000 mg/kg (Other, Rat, Literature study)
LD50 dermal rabbit	10578 mg/kg (Other, Rabbit, Literature study)
LC50 inhalation rat (mg/l)	40 mg/l (Other, 4 h, Rat, Literature study)
ATE US (dermal)	10578 mg/kg body weight
ATE US (vapors)	40 mg/l/4h
ATE US (dust, mist)	40 mg/l/4h

Pseudocumene (95-63-6)	
LD50 oral rat	6000 mg/kg body weight (EU Method B.1 tris: Acute oral toxic – Acute toxic class method, Rat, Male, Experimental value)
LD50 dermal rat	3440 mg/kg (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Read-across)
LC50 inhalation rat (mg/l)	10.2 mg/l air (Other, 4 h, Rat, Male/female, Read-across)
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	18 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Xylene (1330-20-7)	
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : Suspected of causing cancer (Inhalation).

Cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans

Xylene (1330-20-7)	
IARC group	3 - Not classifiable

Aromatic 100

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after ingestion	: Risk of lung edema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.
Ecology - water	: Toxic to aquatic organisms. Contains ground water contaminating component(s). Severe water pollutant (surface water).

Aromatic 100 (64742-95-6)	
EC50 Daphnia 1	3.2 mg/l
ErC50 (algae)	2.9 mg/l
ErC50 (other aquatic plants)	1 mg/l
NOEC chronic fish	9.2 mg/l
Cumene (98-82-8)	
LC50 fish 1	4.8 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	2.14 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
Pseudocumene (95-63-6)	
LC50 fish 1	7.72 mg/l (96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)

12.2. Persistence and degradability

Cumene (98-82-8)	
Persistence and degradability	Biodegradable in the soil. Inherently biodegradable. Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.28 g O ₂ /g substance
Chemical oxygen demand (COD)	2.42 g O ₂ /g substance
ThOD	3.2 g O ₂ /g substance
BOD (% of ThOD)	0.4
Pseudocumene (95-63-6)	
Persistence and degradability	Biodegradable in the soil. Not readily biodegradable in water.
Chemical oxygen demand (COD)	0.44 g O ₂ /g substance

12.3. Bioaccumulative potential

Aromatic 100 (64742-95-6)	
Log Pow	2.1 - 6
Cumene (98-82-8)	
BCF fish 1	35.5 (Carassius auratus)
BCF other aquatic organisms 1	94.69 (BCFBAF v3.00, Calculated value)
Log Pow	3.66 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Pseudocumene (95-63-6)	
BCF fish 1	31 - 275 (Other, 8 week(s), Cyprinus carpio, Weight of evidence)
Log Pow	3.63 - 4.09 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Aromatic 100

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

Cumene (98-82-8)	
Log Koc	2.946 (log Koc, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
Pseudocumene (95-63-6)	
Surface tension	0.029 N/m
Log Koc	3.04 (log Koc, Calculated value)
Ecology - soil	Low potential for mobility in soil. May be harmful to plant growth, blooming and fruit formation.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Do not discharge into drains or the environment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Incinerate under surveillance with energy recovery.
Additional information	: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1268 Petroleum distillates, n.o.s., 3, III
UN-No.(DOT)	: UN1268
Proper Shipping Name (DOT)	: Petroleum distillates, n.o.s.
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242

Aromatic 100

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- DOT Special Provisions (49 CFR 172.102) : 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter.
 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.
 IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
 T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
 TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
 TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

- Transport document description (IMDG) : UN 1268 PETROLEUM DISTILLATES, N.O.S. (Solvent Naphtha), 3, III
- UN-No. (IMDG) : 1268
- Proper Shipping Name (IMDG) : PETROLEUM DISTILLATES, N.O.S. (Naphtha Solvent)
- Class (IMDG) : 3 - Flammable liquids
- Packing group (IMDG) : III - substances presenting low danger
- Limited quantities (IMDG) : 5 L

Air transport

SECTION 15: Regulatory information

15.1. US Federal regulations

Aromatic 100 (64742-95-6)	
SARA Section 311/312 Hazard Classes	Physical hazard – Fire Health hazard - Acute Health hazard - Delayed
Cumene (98-82-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
Product RQ	454545.45 lb
Pseudocumene (95-63-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	

Aromatic 100

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	100 lb
Product RQ	

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

Cumene (98-82-8)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Cumene (98-82-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Cumene (98-82-8)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Pseudocumene (95-63-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

Xylene (1330-20-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:


H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

Aromatic 100

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- | | |
|--------------------|--|
| NFPA health hazard | : 1 - Materials that, under emergency conditions, can cause significant irritation. |
| NFPA fire hazard | : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. |
| NFPA reactivity | : 0 - Material that in themselves are normally stable, even under fire conditions. |



SDS US (GHS HazCom 2012)

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Please be advised revisions to the Safety Data Sheet (SDS) may require a label update. In no event shall Whitaker Oil Company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Whitaker Oil Company has been advised of the possibility of such damages. The vendor assumes no responsibility for injury or damages resulting from the inappropriate alteration or manipulation of this SDS and its contents from that originally submitted by Whitaker Oil Company.