



95% Normal Hexane

Property	Typical Value*	Specification	Test Method
Composition, LV%			Chromatography
2 Methyl Pentane	0.1	Report	
3 Methyl Pentane	0.8	Report	
Normal Hexane	96.5	95.0 Min.	
Methylcyclopentane	2.6	Report	
2,4-Dimethylpentane	trace		
Cyclohexane	trace		
Benzene Content, ppm	<1	Report	ASTM D 3606(Mod)
Distillation Range, Deg. F @ 760 mm Hg			ASTM D 86
Initial Boiling Point	155.1	Report	
Dry Point	156.4	Report	
Specific Gravity @ 60/60 F	0.666	Report	ASTM D 4052
API Gravity @ 60 F	81.0		ASTM D 4052
Density of Liquid @ 60 F, lbs/gal	5.54		ASTM D 4052
Bromine Index, mg/100g	8	Report	ASTM D 1492
Color, Saybolt	+30	+30 Min.	ASTM D 6045
Sulfur Content, ppm	<1	Report	ASTM D 4045
Doctor Test	Negative		ASTM D 235
Copper Corrosion, 2 hr. @ 212 F	1	Report	ASTM D 130

Notice: Since the conditions of handling and use are beyond our control we make no guarantee of results; nor is any of the above information to be taken as a license to operate under, or recommendation to infringe, any patent.

* Note 1 - The information contained herein is, to the best of our knowledge and belief, accurate, but we assume no liability for damages or penalties resulting from use of or reliance on this information.

Packaging Types:

- Truck
- Railcar
- 54 Gallon Drums
- 5 Gallon Pails